

WALL MOUNT FIBER OPTIC TERMINAL BOX

MODEL: OTB-02C

Overview:

DYS Fiber Wall Outlet has the typical 86 x 86mm wall-mounting footprint which is used to contain and cable manage a selection of copper and fiber outlets in a variety of configurations depending on the application required, and designed for use in residential and business applications for the termination of up to eight fibers. The wall box enables the installation of either a single Blown Tube cable using up to a 8 fiber blown unit or 4 fiber Ruggedized cables to be spliced to four SC pigtails (PC or APC) or LC duplex(SC simplex format) which connect to adapters at the base of the unit. The unit can be quickly installed within an office, house or communication room environment.

Picture:



OTB-04C

Main features:

- Ergonomic design.
- Ability to allow cables to enter from rear or bottom of the unit.
- All fibers are positively managed to maintain a 30mm minimum bend radius.
- Optional Removable rear entry cable management.
- Flip tray to allow access to connectorised tails and cable entry.
- Standard colour white. Other colors available on request

Application:

- Fiber to the home (FTTH)
- Fiber to the building (FTTB)
- Local area networks
- Wide area networks

Specifications:

Item	Characteristic
Dimension	86x86x33mm
Maximum Fiber Capacity	4/8
Adaptor	4XSC simplex,4XLC duplex
Cable	900um or Drop cable
Material	ABS
Net weight	58g
Operation temperature	-20°C to + 50°C

Technical Parameters:

Environmental temperature:	-5 °C ~+60°C
Operating temperature:	-5 °C ~+40 °C
Relative humidity:	≤85 % (+30 °C)
Atmosphere pressure:	70~100Kpa
Voltage resistance strength:	>1500V(DC)1 min non-puncture, no are-over

DYSFO

ShenZhen DYS Fiber optic Technology Co.,Ltd

Tel: 86-0755-29518585, 29650336 Fax : 86-0755-29510505 PC/ZIP: 518133

Add: 2/F, 7 Building, Tangtou Industrial Zone 3rd, Shiyan Town, BaoAn District, Shenzhen, P.R China

