

WALL MOUNT FIBER OPTIC TERMINAL BOX

MODEL: OTB-04C

Overview:

Wall-mount Fiber Optic Terminal Box is mainly used for connecting the indoor optical cables, optical patch cords and optical pigtaills. It can be wall mounted or pole mounted, and facilitates the test and refit of the lines.

Picture:



OTB-04C

Main features:

- This box could be used for wall-mounted and applications
- The base and cover of the box adopts “self-clip” plastic, which is easy and convenient to open and close
- Could be used for adaptors such as SC, FC, LC, E2000 ...
- The max capacity is 4 fibers
 - ✓ Fiber Optic Splice Tray: storing fiber connectors (together with the protective components) and the spare fibers
 - ✓ Fixing Device: used for fixing the fiber protective tubes, the fiber reinforced cores and the distribution pigtaills
 - ✓ The brim of the box is sealed
 - ✓ Open type structure, High quality PC, ABS, PPR optional.
 - ✓ Material is anti-burning.

Application:

- Fiber Optic Telecommunication
- Optical Network equipment
- CATV
- High Speed Transmission Systems
- FTTH

Specifications:

Model	Fiber Quantity	Dimension(cm)	Weight(Kg)
OTB-04C	4	150x30x110	0.2

Technical Parameters:

Environmental temperature:	-5 °C ~+60°C
Operating temperature:	-5 °C ~+40 °C
Relative humidity:	≤85 % (+30 °C)
Atmosphere pressure:	70~100Kpa
Voltage resistance strength:	>3000V(DC)1 min non-puncture, no are-over

DYSFO

ShenZhen DYS Fiber optic Technology Co.,Ltd

Tel: 86-0755-29518585, 29650336 Fax : 86-0755-29510505 PC/ZIP: 518133

Add: 2/F, 7 Building, Tangtou Industrial Zone 3rd, Shiyan Town, BaoAn District, Shenzhen, P.R China

