

# HXJY-5030

## Military grade PCM Multiplexer HXJY-5030



### Feature

- Rich E1 and A ports, perfect for network design and wide band application;
- Gateway equipment for E1 and A ports;
- Conversion for E1 and A port;
- A port bit rate: 2048/1024/512/256/128kbps
- 30 voice channels, FXS/FXO/hot line/magenet line configurable, 10 of the voice channels can be set to 4/W;
- 2 10/100BaseT fast Ethernet and 1 V.35;
- 8 RS232 and 4 RS422 asynchronous data
- 1 video,H.264 coding
- 10MHz/2048kbps clock input port,4.6ppm high accurate internal clock
- Voice high compressing module embedded;
- Data channel has error correcting encoder/decoder for bad channel;
- Whole network local/line clock automatic setting;
- 19' 2U electromagnetic compatible and sealed crust;
- Wide temperature rang, perfect for outdoor application;
- LCD display and setting;
- Remote manageable;
- -48V,+24V DC power supply or ~220V AC power supply
- Low power consumption.

### Specifications

Item		Specs
Type	Max number	
E1	4	ITU-T G.703, 64k cross connection
A port	2	2048/1024/512/256/128kbps
FE	2	10/100M half-duplex, full-duplex mode adaptive VLAN priority setting
Voice	30	Automatic telephone; 2100Hz magnet phone; Hotline; 4W voice; 2W voice; Battery Telephone; K port; RS232/485; All supported.
Video	1 bi-direction video + 1 voice + 1 control	Coding: H.264 Interface: 75Ω BNC Bandwidth: 128k~M Compatible: PAL, NTSC
V.35		N*64kbps N range: (1,32)
Power supply		220VAC -48/+24VDC
Temperature		Working temperature (-20°C, 60°C) storage temperature (-55°C70°C)
Power consumption		≤ 50W
Dimension		WxHxD (mm)480x88x365
Weight		Net weight ≤10kg

