



	Product Name	Key Feature
	<p style="text-align: center;"><b>UT-2201</b></p> <p style="text-align: center;"><b>RS-232 to RS-485 600w Surging protection Interface Converter</b></p>	

## INTRODUCED

### I. Summary:

In order to carry through remote digital communication between computers with various standard series interfaces converter facilities or intelligent instruments, it needs inter exchange of standard series interface converter of compatible RS-232C and RS-485 standard is able to convert mono-end RS-232 signal to balance difference RS-485 signal and extend the communication distance to 1.2km. No external power but adopts a particular RS-232 charge pump to drive the system, and gains electricity without initializing the RS-232 series interface. An internal zero delay auto transceiver and particular I/O circuit automatically control the data stream direction instead of an handshake signal (for example RTS, DTR etc). There by in guarantees the function under RS-485 without changing the program compiled under RS-232 half-duplex mode and assures the adaptation to current operation software and interface hardware. The transmission rate of 300-115.2kbps. Is capable of applying between host computers, host computer and its extensions or external equipment and forms dot to dot, dot to dots remote and multi-communication network, It implements multi-machine response communication and commonly used in systems of industrial automation control all-one-card. Door safe, car parking, ATM, bus charge, eatery sell out, staff attendance management, and toll highway etc.

### II. Specification:

- Interface feature: RS-232C,RS-485standard interface compatible with EIA,TIA
- Electric interface: RS-232endDB9holeconnector, RS-485 end
- DB9 needle connector, with connection pole
- Working mode: asynchronism half-duplex difference transmission
- Transmission media: twisted -pair or STP
- Transmission rate: 300-115.2KBPS
- External discharge dimension: 63mmX33mmX17mm
- Working circumstance : - 25to 70 degree C, relative humidity5% to 95%
- Transmission distance: 1,200m(RS-485 end),5m(RS-232 end)

## INFORMATION ORDER

**MODEL: UT-2201** Port-powered, RS-232 to RS-485/422, Mini-size