






	Product Name	Key Feature
	<p style="text-align: center;">UT-2674SM/MM</p> <p style="text-align: center;">10/100TX to SC Type Fiber Optic Industrial Media Converter 4 TCP/IP port</p>	<div style="display: flex; flex-wrap: wrap; justify-content: space-around;"> <div style="text-align: center; margin: 5px;">  Fiber </div> <div style="text-align: center; margin: 5px;">  TCP/IP </div> <div style="text-align: center; margin: 5px;">  Surging Protection </div> <div style="text-align: center; margin: 5px;">  ESD protection </div> </div>

INTRODUCED

I. Summary:

This unit is special designed for data transmission between 100Base-TX and 100Base-FX or FL . Especially suit for smart building or optical to room Auto adapt 10Mbps/100Mbps, easy to upgrade. Extend STP:100M to Optical fiber:100KM, easy for your connection to Server, repeater, hub, terminal

II. Specification:

- Delicate Optical-Electric module, high powered performance,transfer safety, Long life
- Half-duplex, Full-duplex, auto-negotiation
- 10M/100Mbps auto-adapt
- Built-in storage and forward mode,Cache:1MB, multi-protocol supported
- Data package:Max: support:1600 bytes
- Telecommunication quality, MTBF>50k Hours
- Power supply:DC9-48V/500mA reverse connection available;AC 8~38V/560mA
- SC interface(ST,FC optional)
- Surge protection: 3000V(power supply)
- ESD(Electrostatic discharge protection) : 4000V(Ethernet)

INFORMATION ORDER

MODEL: UT-2674 10/100TX to SC Type Fiber Optic Industrial
Media Converter 4 TCP/IP port