





	Product Name	Key Feature
	<p style="text-align: center;">UT-6508</p> <p style="text-align: center;">DNI-Rail 10/100m 8 port unmanaged Ethernet Switches</p>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>ESD protection</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>8</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;"> <p>100M</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>Surging Protection</p> </div> </div>

INTRODUCED

I. Summary:

UT-6508 is a 8-port industrial grade non-managed Ethernet switch with reverse polarity protection of AC or DC input for avoiding being damaged. It has ingenious appearance design and supports industrial standard snap-fit-mounting and wall-mounting installation, so it's very easy to be installed and used in any industrial networks.

II. Specification:

- Network: 10/100Base-TX.
- Ethernet communication distance: up to 100 meters.
- Connector: 5x10/100 Base-TX RJ-45 terminals.

Power specifications:

- DC: 9~48V with reverse polarity protection.
- AC: 9~38V.
- Over-current protection: 1.1A.

Power Consumption:

- With full load: 2.2Watts.
- Dimension: 150mm x 100mm x37.5mm (Lengthx Width x Height).
- Hosing : plastic material.
- ESD(Electrostatic discharge protection): 4000V(Ethernet).
- Surge protection: 3000V(power supply).
- Operating temperature: -10°C ~ 60°C (14~140°F).
- Storage temperature: -55°C ~150°C (-67-3020°F).
- Operating humidity: 5%~95% (non-condensing).
- Storage humidity: 0%~95% (non-condensing).
- CE and FCC approval.

INFORMATION ORDER

MODEL: UT-6508 Ethernet Switches.
DNI-Rail 10/100m 8-port unmanaged.