





	Product Name	Key Feature
	<p style="text-align: center;">UT-6524</p> <p style="text-align: center;">DIN-Rail 10/100m 24 port unmanaged Ethernet Switches</p>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>ESD protection</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>Surging Protection</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;"> <p>100M</p> </div> <div style="border: 1px solid gray; padding: 5px; text-align: center;">  <p>Ethernet 24</p> </div> </div>

INTRODUCED

I. Summary:

UT-6524 is a 24-port industrial grade non-managed Ethernet switch with reverse polarity protection of AC or DC input for avoiding being damaged. It has ingenious appearance design and supports industrial standard snap-fit-mounting and wall-mounting installation, so it's very easy to be installed and used in any industrial networks.

II. Specification:

- Compatibility: standard IEEE 802.3, 802.3u, 802.3x.
- Network: 10/100Base-TX.
- Ethernet communication distance: up to 100 meters.
- Connector: 24x10/100 Base-TX RJ-45 terminals.

Power specifications :

- AC100-240V/50-60Hz.
- Over-current protection: 1.1A.

Power Consumption

- With full load: 5Watts.
- Dimension: 440mm x 201mm x 43mm (Lengthx Width x Height).
- Hosing: Metal material.
- Surge protection: 2000V(power supply).
- Operating temperature: -10°C ~60°C (14~140°F).
- Storage temperature: -55°C ~150°C (-67-302°F).
- Operating humidity: 5%~95% (non-condensing).
- Storage humidity: 0%~95% (non-condensing).
- CE and FCC approval.

INFORMATION ORDER

MODEL: UT-6524 Ethernet switches.
DIN-Rail 10/100m 24-port unmanaged.