


	Product Name	Key Feature
	<p style="text-align: center;">UT-7516</p> <p style="text-align: center;">16-ports PCI to RS232 PCI/PCI-Express to Serial</p>	

INTRODUCED

I. Summary

The UT-7516 is a general use PCI serial port card designed for POS and ATM application. It can be used in industrial automation system manufacturing and system intergration. The UT-7516 provides sixteen RS-232 serial ports and can be connected to equipment with multiple serial ports like PCs, terminal devices, modems, printer, scanners, etc. The data of speed of each port can reach up to 921.6 Kbps and provide a modem control signal which can ensure the compatibility serial port equipment with peripherals. The UT-7516 can work under a 3.3V or 5V PCI bus allowing the serial port card to be installed in any usable PC or server.

II. Specification:

- Hardware Interface
- Connection Type: 1 HDR78 female
- Bus: 32 bit Universal PCI
- Signal RS-232: DCD, RXD, TXD, DTR, GND, DSR, RTS, CTS, RI
- Transmission Speed: 300bps-921.6Kbps
- Data Bit: 5, 6, 7, 8
- Stop Bit: 1, 1.5, 2
- Parity Bit: None, Even, Odd, Space, Mark
- Flow Control: RTS/CTS XON/XOFF
- Operating temperature: -40°C~85°C
- Supporting System: Win98/2000, WinXP/2003/Vista/2008 32/64, DOS/Linux 2.4/2.6

INFORMATION ORDER

MODEL: UT-7516 Multi-Serial Port Card with ESD protection
16-ports PCI to RS232