



	Product Name	Key Feature
	<p style="text-align: center;"><b>UT-752E</b></p> <p style="text-align: center;"><b>2-ports RS232 with ESD protection PCI/PCI-Express to Serial</b></p>	

## INTRODUCED

### I. Summary:

The UT-752E is a general use PCI serial port card designed for POS and ATM application. It can be used in industrial automation system manufacturing and system integration. The UT-754 provides Four RS-232 serial ports and can be connected to equipment with multiple serial ports like PCs, terminal devices, modems, printers scanners, etc. The data speed of each port can reach up to 921.6Kbps and provide a modem control signal which can ensure the compatibility serial port equipment with peripherals. The UT-754 can work under a 3.3V or 5V PCI bus allowing the serial port card to be installed in any usable PC or server.

### II. Specifications:

- Hardware Interface
- Connection Type: 1 DB44 female
- Bus: 32 bit Universal PCI
- Signal RS-232: DCD, RXD, TXD, DTR, GND, DSR, RTS, CTS, RI
- Transmission Speed: 300bps-921.6Kbps
- Data Bit: 5, 6, 7, 8
- Stop Bit: 1, 1.5, 2
- Parity Bit: None, Even, Odd, Space, Mark
- Flow Control: RTS/CTS XON/XOFF
- Operating temperature: -40°C-85°C
- 600W surging protection and ±15KV ESD
- Supporting System: Win98/2000, WinXP/2003/Vista/2008 32/64, DOS/Linux 2.4/2.6

## INFORMATION ORDER

**MODEL: UT-752E**      Multi-Serial Port Card  
 2-ports PCI to RS232 with ESD protection