

| | Product Name | Key Feature |
|--|--|-------------|
| | <p style="text-align: center;">UT-883</p> <hr/> <p style="text-align: center;">1-port USB to RS-232 Serial Converter</p> | |

INTRODUCED

I. Summary:

USB to serial port, you can easily establish a reliable Connections between serial (RS-232) and USB interface. Through the use of a plug-and-play USB interface and hot pluggable capability and can be addressed to the serial port (RS-232) peripherals provide very easy-to-use environment. The design makes you to easily connect with as mobile phones, digital cameras, ISDN - TA, modem, and other equipment, and provide up to 1 Mbps Speeds.

II. Specification:

- Fully compatible with USB (Universal Serial Bus) VER: 2.0
- Support for RS-232 interface
- The standard DB9 serial needle
- Serial transmission speed up to 1Mbps
- Support automatic handshake agreement
- Support remote wake-up and power management
- With USB Direct power supply, do not need additional power supply
- Wires: 1.5 meters long, with magnetic ring filtering, anti-interference, with shielding function, 64-pin.
- The ASIC chip can support USB port to the serial port communication.
- Transmission distance: 5m
- Working circumstance: - 25 to 70 degree ,Celsius Relative humidity 5% to 95%
- Support Windows95/98/2000/XP/Vista/Server2003/Mac OS-X/OS9, Linux

INFORMATION ORDER

MODEL: UT-883 1-port USB to RS-232 Serial Converter with ESD protection