

## SFP BIDI 1.25G 1310/1550nm(1550/1310nm) DDM 60KM Transceiver

**MODEL: SFP-BIDI-260**



### PRODUCT FEATURES

- Up to 1.25Gb/s data links
- DFB laser transmitter and PIN photo-detector
- Up to 60km on 9/125μm SMF
- Hot-pluggable SFP footprint
- BIDI SC/UPC type pluggable optical interface
- Low power dissipation
- Metal enclosure, for lower EMI
- RoHS compliant and lead-free
- Single +3.3V power supply
- Support Digital Diagnostic Monitoring interface
- Compliant with SFF-8472
- Case operating temperature
  - ✓ Commercial: 0°C to +70°C
  - ✓ Extended: -10°C to +80°C
  - ✓ Industrial: -40°C to +85°C

### APPLICATIONS

- Switch to Switch Interface
- Fast Ethernet
- Switched Backplane Applications
- Router/Server Interface
- Other Optical Links

### INFORMATION ORDER

Product part Number	Data Rate (Gbps)	Media	Wavelength (nm)	Transmission Distance(km)	Temperature Range ( Tcase ) ( °C )	
SFP-BIDI-260	1.25	Single mode Fiber	1310/1550(1550/1310)	60	0~70	Commercial

SFP-BIDI-260E	1.25	Single mode Fiber	1310/1550(1550/1310)	60	-10~80	Extended
SFP-BIDI-260A	1.25	Single mode Fiber	1310/1550(1550/1310)	60	-40~85	industrial

**Due to continuous improvement, all products specifications are subject to change without further notice.  
Contact us for custom requirements. E-mail: [Sales@zhtelecomm.com](mailto:Sales@zhtelecomm.com) Website: [www.zhtelecomm.com](http://www.zhtelecomm.com)  
Tel: +86-01081593787 Fax: +86-01081593789**