



HD Wireless Day & Night Network Camera

The Edimax IC-3140W 720p wireless network camera is a versatile monitoring device ideal for monitoring your home, shop or factory during the daytime or at night. With Edimax Plug-n-View technology, no complicated setup is required and you can easily connect the camera to the cloud and monitor remotely from a smartphone, tablet or laptop.

The IC-3140W features two-way audio, a motion & sound detection system, built-in microphone & speaker and a MicroSD/SDHC card slot. Motion detection can be configured according to user-defined areas and additionally utilizes a passive infrared sensor (PIR). Motion and audio-triggered snapshots and recording ensure that you capture any illicit or suspicious activity and the wireless user interface allows for easy installation and monitoring.

Plug-n-View for 24/7 Easy Remote Monitoring

Edimax Plug-n-View technology makes it easy for you to keep an eye on your yard, garage, shop, factory or other assets wherever you go. With Plug-n-View technology, you can connect your network camera to the cloud in a few simple steps and access it remotely with a smartphone, tablet, or computer no matter where you are.



EdiView II



Free App

Download on the
App Store

ANDROID APP ON
Google play



Free EdiView II viewer app
for iPhone & Android phones

Night Vision

With a light sensor, image sensor and four infrared LEDs, the IC-3140W is well equipped to meet indoor security and surveillance needs - even in low-light and night-time conditions. And with automatic ICR (IR Cut Filter Removal), infrared light is filtered out during the day time (while allowed to pass at night) ensuring exceptional video color quality at all times.



4 IR LEDs
Image Sensor & ICR




Light Sensor

HD Wireless Day & Night Network Camera

IC-3140W

PIR & Motion Detection Triggered Snapshots & Recording

The powerful built-in motion detection system, with pre-defined detection regions and passive infrared (PIR) temperature sensor, offers peace of mind that you will capture any illicit activity. The PIR sensor detects motion via infrared radiation caused by temperature changes and when motion is detected, the network camera will produce snapshots or video footage of the event immediately – storing the data on a MicroSD/SDHC card or sending it automatically via email or ftp.




Sound Detection Triggered Snapshots & Recording

The IC-3140W also features sound detection capabilities with a built-in microphone. When sound is detected, the network camera will take snapshots or video footage of the event immediately in the same manner as with motion detection, and store the files locally on a MicroSD/SDHC card or send via email or ftp. Integrated sound offers a further level of security than motion-detection and visual imaging alone, providing critical real-time or post-event information about a situation, particularly in scenarios where events occur outside the camera's field of vision. The sounds of breaking windows, doors or anything else suspicious can still be registered even in situations where the event can't be seen.



Push Notifications & Video Alerts

Push notifications are triggered by PIR, sound or motion detection, and when a detection system is triggered, the IC-3140W additionally sends snapshots or video alerts to email or microSD card. If the camera ever goes offline, push notifications are also sent when the camera comes back online to keep users informed about any unusual activity.



HD Wireless Day & Night Network Camera

IC-3140W

Two-Way Audio

The network camera incorporates a speaker and microphone for two-way audio support, so you can remotely communicate at the camera's location or activate a deterrent alarm - a vital, cost-saving and potentially even life-saving additional security tool.



High Quality Videos

The IC-3140W is built with a wide F2.0 lens which covers an impressive diagonal viewing angle of 78 degrees. With a megapixel CMOS sensor, the network camera is able to capture 720p (1280 x 720) videos at 24 frames per second.



MicroSD/SDHC Card Slot for Local Storage


A built-in MicroSD/SDHC card slot supports cards up to 32GB for local storage and backup.




SOFTWARE FEATURES

- Easy remote monitoring via iPhone, iPad, Android, PC & Mac
- High-speed H.264 & MJPEG video compression
- Motion & sound detected snapshots or video to SD card, ftp or email
- Pre- & post-recording upon detected motion
- Viewer software to access 16 network cameras simultaneously
- Manual/scheduled/cycle recording

Keep An Eye On What You Care About The Most




Anywhere & Anytime




Three Steps for Easy Smartphone Setup

- 1 Power on network camera.



- 2 Download the EdiView II app from the App Store or Google Play.




- 3 Pair the camera with your App & Wi-Fi and watch a live stream from anywhere!

HD Wireless Day & Night Network Camera

IC-3140W
TECHNICAL SPECIFICATIONS

Function	Management	Interface
<ul style="list-style-type: none"> Easy remote monitoring via iPhone, iPad, Android, PC & Mac 78 degree diagonal viewing angle Supports dynamic DNS service IR filter embedded Built-in microphone and speaker for two-way audio Built-in Passive infrared (PIR) sensor for enhanced motion detection Motion/sound detection recording and alerts to MicroSD/SDHC card, email and FTP MicroSD/SDHC card slot for local storage 	<ul style="list-style-type: none"> EdiView Finder (Windows/Mac) 16-channel viewer Web management interface Firmware upgradable iPhone & iPad viewer app Android viewer app 	<ul style="list-style-type: none"> Ethernet (RJ-45) port Power jack Reset/WPS button Internal antenna Micro SD/SDHC card slot Passive infrared (PIR) sensor Light sensor Microphone Speaker IR LEDs: 4 LED indicators: Internet, LAN/Wi-Fi LNK/ACT, Power
Video	Video Settings	Supported Protocols
<ul style="list-style-type: none"> High-speed H.264 & MJPEG video compression 1280 x 720 up to 24 fps 640 x 480 up to 30 fps 320 x 240 up to 30 fps 	<ul style="list-style-type: none"> Resolution: HD (1280 x 720), VGA (640 x 480), QVGA (320 x 240), Frame rate: 5, 10, 15, 20, 24 or 30 fps 	<ul style="list-style-type: none"> IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE
Standards	RF Output Power	IR LEDs
<ul style="list-style-type: none"> Fast Ethernet IEEE 802.3/802.3u Wireless IEEE 802.11b/g/n 	<ul style="list-style-type: none"> 11b: 16dBm–18dBm 11g: 14dBm –16dBm 11n: 11dBm –13dBm 	<ul style="list-style-type: none"> IR LEDs for night illumination up to 15 feet
Memory	Operating Conditions	Power
<ul style="list-style-type: none"> 8MB flash 64MB SDRAM 	<ul style="list-style-type: none"> 0–40°C Humidity: 20–80% RH (non-condensing) 	<ul style="list-style-type: none"> 12V DC x 1A
Dimensions	Weight	Certifications
<ul style="list-style-type: none"> 65 x 110 x 27.2 mm 	<ul style="list-style-type: none"> 110g 	<ul style="list-style-type: none"> FCC,CE

APPLICATION DIAGRAM

HARDWARE INTERFACE


Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.

Copyright © 2014 Edimax Technology Co. Ltd. All rights reserved.