

	Product Name	Key Feature
	<p style="text-align: center;">UT-T101 5KA Control Signal Surge Protector RJ11</p>	  

INTRODUCED

I. Summary

The UT-T101 has to be installed by authorized professional person, to avoid incorrect installation or application to influence the normal working and lightning protection of devices, used in over-voltage protection from lightning and EMP of network equipments, like SWITCH, HUB, ROUTER, etc

II. Specification:

Model	UT-T101	UT-T201
Rated operating voltage (Un)	190 V	330 V
Max. DC operating voltage (Uc)	190 V	330 V
Max. AC operating voltage (Uc)	130 V	230 V
Nominal operating current (IL)	0.12 A	0.12 A
Nominal discharge current (8/20 us) (In)	3 KA	5 KA
Maximum discharge current (In)	5 KA	10 KA
Limiting voltage (Upl)	≤330 V	≤510 V
Series impedance characteristic of wire (Ro)	10 Ohm	10 Ohm
Wire-to-wire capacitance (Cll)	≤160 pF	≤160 pF
Wire-to-earth capacitance (Cpe)	≤160 pF	≤160 pF
Response time (ta)	<1 ns	<1 ns
Range of operating temperature	-40°C ~ 85°C	-40°C ~ 85°C
Testing standard	IEC61000-4-5	IEC61000-4-5
Testing level	X	X
Insulation resistance	>1 MΩ	>1 MΩ
Insertion loss (dB)	≤0.5 dB	≤0.5dB
Enclosure protection class	IP30	IP30
Overall dimension	25 x 25 x 82	25 x 25 x 82
Enclosure material	Shielded metallic aluminum	Shielded metallic aluminum
Type of wiring	Connection terminal (RJ11)	Connection terminal (RJ11)
Anti-static level	Class 4	Class 4
Transmission rate (bps)	10 M	10 M

Operating Environment

Temperature: -40°C ~ 85°C;

Relative humidity: 5% ~ 95%;

Barometric pressure: 70 kPa ~ 106 kPa

INFORMATION ORDER

MODEL: UT-T101 5KA Control Signal Surge Protector RJ11